Acknowledged globally





Item Number 4688541

REFVAC-RC

The REFVAC-RC is the optimal device for checking the evacuation process on the construction site or in the laboratory. The device scores with its high accuracy and communicates wirelessly with the REFMESHTM App and the REFMATETM, so that long-term measurements are possible with it. With the help of the REFMESHTM, all measured values are compiled in a detailed report.

- Integrated display
- · High precision
- High resolution in low vacuum
- Wireless communication
- Signal range 300 ft
- Intuitive handling
- Flexible power supply

Technical Data

Material	Brass ABS Polycarbonate FR-4	
Color	yellow (RAL 1023) green (RAL 6026)	
Standards	CE / FCC / IC / RCM / RoHS / REACH	
RoHS Conformity	Yes	
Working Pressure	435 psi	
Gas Connection	1/4" SAE	
Pressure Scale	Pa Torr inHg mTorr mbar micron psi	
Pressure Range	atm - 0 micron	
Resolution	0.1 micron	
Battery	3 x AAA	
Operating Hours	> 100	

Acknowledged globally



Pressure Type	Absolute Pressure	
Scope of Supply	Batteries Pouch Quick Guide Calibration Certificate Filter	
Packaging	Blister	
Sensor type	Pirani Sensor	
Accuracy	±5% of reading or ±10micron: From 10 to 10'000 micron	
	±10% of reading: From 10'000 to 30'000 micron	
	Indication: From 30'000 micron to atm	

Accessories

4687845	REFVAC-T	Forged female flare branch tee connection: 3 x 1/4" SAE, with O-ring
4687631	SWIVEL-ARM- 1/4"SAE-N	Swivel arm for vacuum gauge, 1/4" SAE
4688477	VCL-60- 3/8"SAEx1/4"SAE	Vacuum hose 3/8" SAE x 1/4" SAE, 60"/150cm
4687701	32525	Valve core replacing tool, 1/4"SAE
4687740	32525-5/16"SAE	Valve core replacing tool, 5/16"SAE
4503635	EZ-125/12	Sealant, 12 pieces per package

Spare Parts

4688566	REFVAC- FILTER/5	Replacement filter for REFVAC-RC, 5 pieces
4676110	NFT5-4-K-GREEN	Seal flare cap 1/4" SAE