ENGINEERING TOMORROW



Flyer | SVL Flexline®

Raising the bar for **SVL Flexline®**

Danfoss is pleased to introduce a new range of SVL valves approved up to 65 bar and has a temperature range from - 60° c to 150° c. The characteristics of the new valve makes it perfectly suited for the requirements of industrial ammonia (R717) heat recovery systems as well as sub critical CO_2 (R744) systems.





The SVL 65 valves approved for 65 bar are perfectly suited for the requirements of industrial ammonia (R717) heat recovery systems and sub critical CO_2 (R744) systems.

Using a higher pressure has several advantages. For sub critical CO_2 systems, the higher pressure means that smaller stand-still units can be used or left out entirely as the saturation temperature rises from 16°C to 25,5°C. Furthermore, the higher pressure enables hot gas to be taken from the transcritical side.

For ammonia heat pumps the higher pressure allows for a rise in the saturation temperature from 90°C to 102°C. This means you can have same capacity with fewer compressors and a higher supply temperature which enables the water to be used in a broader application range.

The valve is based on the acknowledged SVL platform which above all is characterized by flexibility. Using just two basic

valve housings – a straightway and an angle way – the platform offers five different functions. You will find that this simplicity offers you easy and time saving usage in many processes.

Danfoss Flexline™ products offer an easy road to sustainability with low life cycle costs, low emissions from leaks and approvals for use with low GWP refrigerants.

Features and benefits

- Handles wide temperature range from -60 to +150°C [-76 to 302°F]
- Handles working pressure up to 65 bar (943 psi)
- Offers you one common housing that allows easy and time saving switch between the functions
- Delivers a smooth opening and closing operation along with very high reliability
- Handles constant high temperatures in R717 Heat Pumps with special replacement kit.

SVL overview parts and complete valves

| Size | Parts Production | | | | | | | | | | | Replacement | |
|--------|------------------|----------|----------|----------|--------------|----------|----------|----------|----------|----------|----------|---------------|----------|
| | Housing | | | | Top complete | | | | | | | . kit | |
| | ANG | | STR | | SVA-S | SVA-L | | | | | | For R717 | for |
| | DIN | ANSI | DIN | ANSI | (cap) | (cap) | SCA-X | CHV-X | REG-SA | REG-SB | FIA | heat pumps | R1270 |
| DN 6 | 148B6689 | 148B6687 | 148B6693 | 148B6691 | 148B6695 | | | | | | | | |
| DN 10 | 148B6690 | 148B6688 | 148B6694 | 148B6692 | 14880095 | | | | 148B5761 | 148B5764 | | 148B6084 | 148B6085 |
| DN 15 | 148B6622 | 148B6612 | 148B6642 | 148B6632 | 148B6652 | 148B6659 | 148B5769 | 148B5776 | 148B5762 | 148B5765 | 148B5783 | 148B6070 | 148B6077 |
| DN 20 | 148B6623 | 148B6613 | 148B6643 | 148B6633 | | | | | | | | | |
| DN 25 | 148B6624 | 148B6614 | 148B6644 | 148B6634 | 148B6653 | 148B6660 | 148B5770 | 148B5777 | 148B5763 | 148B5766 | 148B5784 | 148B6071 | 148B6078 |
| DN 32 | 148B6625 | 148B6615 | 148B6645 | 148B6635 | | | | | | | | | |
| DN 40 | 148B6626 | 148B6616 | 148B6646 | 148B6636 | | | | | | | | | |
| DN 50 | 148B6627 | 148B6617 | 148B6647 | 148B6637 | 148B6654 | | 148B5771 | 148B5778 | | 148B5767 | 148B5785 | 148B6072 | 148B6079 |
| DN 65 | 148B6628 | 148B6618 | 148B6648 | 148B6638 | 148B6655 | | 148B5772 | 148B5779 | | 148B5768 | 148B5786 | 148B6073 | 148B6080 |
| DN 80 | 148B6629 | 148B6619 | 148B6649 | 148B6639 | 148B6656 | | 148B5773 | 148B5780 | | | 148B5787 | 148B6074 | 148B6081 |
| DN 100 | 148B6630 | 148B6620 | 148B6650 | 148B6640 | 148B6657 | | 148B5774 | 148B5781 | | | 148B5788 | 148B6075 | 148B6082 |
| DN 125 | 148B6631 | 148B6621 | 148B6651 | 148B6641 | 148B6658 | | 148B5775 | 148B5782 | | | 148B5789 | 148B6076 | 148B6083 |
| DN 150 | | | | | | | | | | | | | |
| DN 200 | | | | | | | | | | | | | |

| Size | Complete valve | | | | | | | | | | | |
|--------|----------------|----------|----------|----------|----------|----------|----------|----------|--|--|--|--|
| | | SVA | (cap) | | FIA | | | | | | | |
| Size | AN. | NG | S | ΓR | AN. | NG | STR | | | | | |
| | DIN | ANSI | DIN | ANSI | DIN | ANSI | DIN | ANSI | | | | |
| DN 150 | 148B6665 | 148B6667 | 148B6666 | 148B6668 | 148B6669 | 148B6671 | 148B6670 | 148B6672 | | | | |
| DN 200 | 148B6673 | 148B6675 | 148B6674 | 148B6676 | 148B6677 | 148B6679 | 148B6678 | 148B6680 | | | | |

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary in specifications already agreed.
All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss AVS. All rights reserved.